

BED TYPE MILLING MACHINE DEBER MOD.BTM-3000 CNC UNIT SELCA 3040



TECHNICAL CHARACTERISTICS

TABLE

• table size	mm.	3500x600
• number of T slots	n°	5
• width of T slots	mm.	18
• pitch of T slots	mm.	125
• max load permitted on the table	Kg.	5500

FEEDS & TRAVEL

• X axis travel	mm.	2500
• Y axis travel	mm.	1000
• Z axis travel	mm.	850
• ram travel	mm.	400
• rapid feed	mm/min	8000
• working feed	mm/min	10-8000
• motor power axis	Nm	14

SPINDLE

Dimensions and technical data are not demanding and can be changed at the discretion of the Manufacturer



SKIO Macchine Srl - 36010 Zanè (VI) - Italy Via M.Pasubio, 160
Tel. 0445 575720 fax 0445 501480 - C.F. e P.IVA 03981830247
Reg. Impr. 03981830247 - REA 369740 - Cap. Soc. I.V. € 40.000
TECHNOLOGY - MACHINE TOOLS - CUSTOMER CARE

www.skio.net

info@skio.net

• motor power	HP	25
• speed ranges with manual selection	n°	27
• spindle speed	rpm	18-2120
• spindle nose	ISO	50
• diameter of front bearing	mm.	110

GENERAL DATA

• hydraulic power unit	HP	1
• lubrication motor pump	HP	0,12
• coolant pump	HP	0,18
• approx weight	Kg.	13500



SKIO Macchine Srl - 36010 Zanè (VI) - Italy Via M.Pasubio, 160
Tel. 0445 575720 fax 0445 501480 - C.F. e P.IVA 03981830247
Reg. Impr. 03981830247 - REA 369740 - Cap. Soc. I.V. € 40.000
TECHNOLOGY - MACHINE TOOLS - CUSTOMER CARE

www.skio.net

info@skio.net

STANDARD ACCESSORIES

- Machine retrofited with CNC Selca 3040
- Universal milling head
- Lubrication system
- Coolant system
- Year of construction 1986