

VERTICAL MILLING MACHINE PHOEBUS WICKER MOD.EVS 300AL**TECHNICAL CHARACTERISTICS****SPINDLE**

• spindle speed at first range	rpm	480
• spindle speed at second range	rpm	3600
• quill diameter	mm.	110
• spindle motor	HP	5
• spindle nose	ISO	40
• quill travel	mm.	140
• quill feed	mm/min	0,035-0,07

X AXIS

• ballscrews diameter	mm.	32
• X axis travel	mm.	1100/1150
• rapid feed	mm/min	3600
• motor power X axis	HP	1

Y AXIS

• ballscrews diameter	mm.	32
-----------------------	-----	----

TECNOLOGY - MACHINE TOOLS - CUSTOMER CARE SERVICE

www.olidali.com - info@olidali.com

www.skio.net - info@skio.net

• Y axis travel	mm.	350/390
• rapid feed	mm/min	2100
• motor power Y axis	HP	1

Z AXIS

• ballscrews diameter	mm.	38
• Z axis travel	mm.	430/510
• rapid feed	mm/min	1000
• motor power Z axis	HP	1,15

WORK TABLE

• working surface	mm.	1470x300
• T slot length	mm.	16
• number of T slots	n°	3
• pitch of T slots	mm.	63

GENERAL DATA

• weight machine	Kg.	1700
• floor space	mm.	1740x1540
• height machine	mm.	2330

STANDARD ACCESSORIES

- X and Y axis ballscrews
- Hardened and ground guideways with covering of Turcite
- Work light
- Auto lubrication system
- Coolant system
- Splash guard
- CE Mark
- Operator and maintenance manuals