

RADIAL DRILLING MACHINE INVEMA MOD.FR65X1600



TECHNICAL CHARACTERISTICS

• drilling capacity in steel	mm.	65
• drilling capacity in cast iron	mm.	75
• tapping capacity in steel	mm.	65
• tapping capacity in cast iron	mm.	75
• quill diameter	mm.	108
• quill travel	mm.	340
• quill inside taper	C.M.	5
• number of speeds	n°	24
• spindle speed	rpm	30-2000
• feed speed	n°	12
• range feed speed	mm/giro	0,08-0,70
• spindle motor	KW	5,5
• arm lifting motor power	KW	3
• coolant pump	KW	0,06
• hydraulic power unit	KW	0,75
• floor space	mm.	2530x950
• height machine	mm.	3190



OLIDALI GROUP Srl - 36016 Thiene (VI) - Italy Via dei Pini, 27/C
Tel. +39 (0) 445 628161 VAT IT 04068850249
Reg. Impr. 04068850249 - REA VI-376594 - Cap. Soc. I.V. € 30.000



TECNOLOGY - MACHINE TOOLS - CUSTOMER CARE SERVICE

www.olidali.com - info@olidali.com

www.skio.net - info@skio.net

STANDARD ACCESSORIES

- Fixed cube
- Hydraulic system
- Coolant system
- Hydraulic clamping
- Operator and maintenance manuals