

Specifications

Specifications	Unit	Linmax B-22	Linmax B-25	Linmax B-30	Linmax B-35	Linmax B-40
Mold		2232/2240/2200	2540/2550/2500	3050/3060/3000	3550/3560/3500	4050/4060/4000
X-axis Travel	mm	3200/4000/∞	4000/5000/∞	5000/6000/∞	5000/6000/∞	6000/8000/∞
Y-axis Travel	mm	2200	2500	3000	3500	4000
Z-axis Travel	mm	1250	1250	1250	1250	1250
Table						
Table long	mm	3200/4000/∞	4000/5000/∞	5000/6000/∞	5000/6000/∞	6000/8000/∞
Table width	mm	2000	2200	2700	3200	3700
T-slot size (width)	mm	28				
Table load	Kg/m²	5000				
Distance between spindle nose	mm	200-1450	200-1450	200-1450	200-1450	200-1450
Distance between column	mm	3290	3590	4090	4590	5090
Feedrate						
X/Y/Z-axis rapid feedrate	m/min	60/60/50	60/60/50	60/60/50	60/60/50	60/60/50
Auto tool changer						
Tool shank	type	HSK A63	HSK A63	HSK A63	HSK A100	HSK A100
Tool magazine capacity	pcs	30	30	30	30	30
Max. tool weight	kgs	8	8	8	15	15
Max. tool length	mm	350	350	350	350	350
Max. tool dimensions	mm	Ø 75	Ø 75	Ø 75	Ø 125	Ø 125

∞=or more

The Company reserves the right to change, with all the technical specifications of the contract-based technology.