

USED BED TYPE MILLING MACHINE MTE SELCA 4045 MOD.BF-3200 CNC UNIT SELCA S-4045P



TECHNICAL CHARACTERISTICS

TABLE

• length	mm.	3200
• width	mm.	1000
• number of T slots	n°	7
• T slot size	mm.	22
• pitch of T slots	mm.	140
• table load	Kg.	11000

TRAVELS

• X axis travel	mm.	3000
• Y axis travel	mm.	1200
• Z axis travel	mm.	1500

FEEDS

• working feed	mm/min	0-12000
• rapid feed	mm/min	15000



SKIO s.r.l. - 36010 Zanè (VI) - Italy - Via Monte Pasubio, 160
Tel. 0445 575720 fax 0445 501480 - C.F. e P.IVA 02750400240

TECHNOLOGY - MACHINE TOOLS - CUSTOMER CARE

www.skio.net

info@skio.net

SPINDLE

• spindle nose	ISO	50
• speed ranges	n°	3
• spindle speed	rpm	40-3000
• spindle motor	KW	30

UNIVERSAL AUTOMATIC HEAD

• slowly vertical guideline degree 2,5°	n°	144
• guideline slanted plan 45° degree 2,5°	n°	144

GENERAL DATA

• floor space	mm.	8014x4047
• height machine	mm.	3075
• approx weight	Kg.	19000



SKIO s.r.l. - 36010 Zanè (VI) - Italy - Via Monte Pasubio, 160
Tel. 0445 575720 fax 0445 501480 - C.F. e P.IVA 02750400240

TECHNOLOGY - MACHINE TOOLS - CUSTOMER CARE

www.skio.net

info@skio.net

STANDARD ACCESSORIES

- Splash guard
- Universal automatic head at 144 division (one every 2,5°) on two joints
- Coolant system
- Thermosond to avoid elongation of the Ram
- Rigid tapping
- Coolant through spindle high pressure 8 bar DIN 69871 with paper filter
- Work light
- Heat exchanger electrical cabinet
- Preparation to install the 4th axis
- Spacer of 150mm between base and column
- Tool magazine with 80 positions chaine type exchange in horizontal / vertical
- Chip conveyor scraper type
- Operator and maintenance manuals
- CNC manuals
- Year of construction 2001
- 4th axis rotary table continues Spirsin diameter mm. 800 with tailstock