

BED TYPE VERTICAL MILL PHOEBUS WICKER MOD.VST1200



TECHNICAL CHARACTERISTICS

VERTICAL SPINDLE

• infinitely variable rotation speed with inverter	rpm	480-3600
• spindle motor	HP	5
• spindle nose	ISO	40
• quill travel	mm.	140

X AXIS

• ballscrews diameter	mm.	32
• travel (auto/manual)	mm.	1220/1230
• working feed	mm/min	0-3000
• motor power	KW	0,85

Y AXIS

• ballscrews diameter	mm.	32
• travel (auto/manual)	mm.	540/580
• working feed	mm/min	0-4300
• motor power	KW	0,85

TECNOLOGY - MACHINE TOOLS - CUSTOMER CARE SERVICE

www.olidali.com - info@olidali.com

www.skio.net - info@skio.net

Z AXIS

● ballscrews diameter	mm.	32
● travel (auto/manual)	mm.	600/600
● working feed	mm/min	0-3000
● motor power	KW	0,85

WORK TABLE

● maximum load allowed on the table	Kg.	250
● working surface	mm.	1470x350
● number of T slots	n°	3
● T slot width	mm.	18

GENERAL DATA

● weight machine	Kg.	4600
● floor space	mm.	2400x2000
● height machine	mm.	2500

STANDARD ACCESSORIES

- Ballscrews on 3 axes
- Fast head with electronic speed variation via Inverter
- Pneumatic air power drawbar
- Safety protections to CE standards
- Continuously variable feeds on axis
- Halogen lamp
- Automatic axis lubrication system
- Coolant system
- Tank for chips and coolant
- CE Mark
- Operator and maintenance manuals